

# **Metropolitan Construction Specification**

### Doors and drawer front:

Doors on the Metropolitan line are made of solid wood rails with a MDF/veneered center panel to reduce the possibility of shrinkage.

## Metropolitan Door Series:

The five piece Metropolitan traditional overlay door has a  $\frac{1}{2}$ " thick MDF/birch veneered raised center panel captured in a  $\frac{1}{2}$ " x 2" solid frame and is complimented with a slab drawer front. All doors and drawer fronts are back beveled so no handles or knobs are necessary.

## Hinges:

6-way adjustable, concealed hinges open at 110 degree on all product lines.

#### Drawers:

The Metropolitan line includes a 5/8" thick solid birch dovetail drawer box with a 3/8" plywood bottom, attached to under mounted epoxy coated slides.

## Shelving:

5/8" thick select veneered plywood with matching wood edge banding is used on all wall and base cabinetry where applicable. The adjustable shelves are supported by plastic self locking shelf clip.

## Backs, Tops and Bottoms:

½" thick veneered plywood, with natural finished interiors. The backs are glued, stapled ad screwed into place for additional support.

### Face Frame:

¾" x 1 ½" solid wood stiles and rails jointed with glue and dowels. Back of face frames are grooved to accept side panels.


### Toe Kick:

½" x 4½" select veneered plywood toe kick is added to each assembled cabinet and stained to match along with the edges. Additional 8' lengths of ½" plywood toe kicks are available for those who do not which to see the joints between cabinets.


### Corner Blocks:


All four corners of the base cabinets are secured with a plastic block fastened to each end panel for support and mounting of a counter top.


- 1) Solid wood door frames mortise and tenon.
- 2) 6-way adjustable concealed hinge with 110 degree opening capability
- 3) 5/8" solid birch dovetail drawer with under mount epoxy coated slides.
- 4) ¾" x 1 ½" solid wood face frame.
- 5) ½" select veneered plywood back with a natural finished interior.
- 6) ½" select veneered plywood side panels grooved into face frame.
- 7) 5/8" select veneered plywood adjustable shelving with matching wood veneer edge banding.
- 8) ½" x4 ½" select veneered plywood toe kick stained to match exterior finish and attached to cabinet.
- 9) Plastic corner blocks added for additional strength and stability and for support and mounting Of countertop.


























CUT ITEMS	ITEM	DESCRIPTION
	CUT-BASE	Reduce depth of base cabinet (min. depth 12")
	CUT-DBASE	Reduce depth of drawer base cabinet (min. depth 12")
	CUT-SBASE	Reduce depth of sink base cabinet (min. depth 12")
	CUT-WALL	Reduce depth of wall cabinet (no min.)
	CUT-TALL	Reduce depth of tall cabinet (no min.)
	CUT-DOOR	Cut out center panel of door for glass insert (per door)
	CUT-DRAWER	Remove cabinet drawer to create false drawer front

PIPE CHASE	ITEM	DESCRIPTION
	CHASE -BASE	Make chase in base cabinet (must supply drawing)
	CHASE-TALL	Make chase in tall cabinet (must supply drawing)
	CHASE-WALL	Make chase in wall cabinet (must supply drawing)

MODIFICATIONS	ITEM	DESCRIPTION
	CLOSE-BLIND	Close open section of a blind wall or base cabinet
	ATTACH-TK	Attach toe kick on wall cabinet
	RECESS-TK	Recess toe kick of base cabinet (must supply a drawing
	CUT-TK	Reduce toe kick height (no min.)
	HAMPER	Install door mounted pull out wood hamper in cabinet
	TILT-OUT	Install tilt out sink base cabinet (tilt not included)
	EDGE-BAND	Additional edge banding (price per linear foot)
	INSTALL-ACCES	Install any accessory in a cabinet ( accessories not included
	INCREASE-WALL	Increase depth on wal cabinet (call for quote)
	SHELF-12	Loose 12" deep shelf (specity cabinet size)
	SHELF-24	Loose 24" deep shelf (specify cabinet size)